CITY WIDE HOME INSPECTORS

PRE-SALE HOME INSPECTION REPORT



68 Cezanne Trail, Thornhill, Ontario

Report Number: 24060390

Inspection Date: 2024-06-05

Prepared by: City Wide Home Inspectors

PO Box 325

Tottenham, Ontario, LOG 1W0

Website: www.cwhi.ca

Inspector: Michael Fournier

Email: mike@cwhi.ca

Copyright © 2024 2061490 Ontario Inc. o/a City Wide Home Inspectors

City Wide Home Inspectors PO Box 325 Tottenham, Ontario, L0G 1W0 Phone: 416-831-6548

email: mike@cwhi.ca www.cwhi.ca



June 7, 2024

Inspection Address: 68 Cezanne Trail, Thornhill, Ontario

Report Number: 24060390

At your request, an inspection of the above property was performed on 2024-06-05. City Wide Home Inspectors is pleased to submit the enclosed report. This report is a professional opinion based on a visual inspection of the accessible components of the home. This report is not an exhaustive technical evaluation. An evaluation of this nature would cost many times more.

Please understand that there are limitations to this inspection. Many components of the home are not visible during the inspection and very little historical information is provided in advance of the inspection. While we can reduce your risk of purchasing a home, we cannot eliminate it, nor can we assume it. Even the most comprehensive inspection cannot be expected to reveal every condition you may consider significant to ownership. In addition to those improvements recommended in our report, we recommend that you budget for unexpected repairs. On average, we have found that setting aside roughly one percent of the value of the home on an annual basis is sufficient to cover unexpected repairs.

The Standards of Practice prohibits us from making any repairs or referring any contractors. We are not associated with any other party to the transaction of this property, except as may be disclosed to you.

The information provided in this report is solely for your use. City Wide Home Inspectors will not release a copy of this report without your written consent.

Thank you for selecting our company. We appreciate the opportunity to be of service. Should you have any questions about the general condition of the house in the future, we would be happy to answer these. There is no fee for this telephone or email consulting. Our fees are based on a single visit to the property. If additional visits are required for any reason, additional fees may be assessed.

Sincerely.

Michael Fournier, Owner City Wide Home Inspectors Certified Master Inspector, CMI Certified Mould Inspector, IAC2

Certified Commercial Property Inspector, CCPI

Certified Infrared Camera Property Inspector, CICPI

BUILDING DATA

BUILDING DATA

Approximate Age: 15 to 20 yrs

Building Type: Single Family Detached

Building Style: Two Story General Appearance: Satisfactory

Main Entrance Faces: For the sake of this report East

Weather Condition: Overcast
Temperature: 20 to 30 C
Ground cover: Dry
Occupancy: Occupied

REPORT LIMITATIONS

This report is intended only as a general guide to help the client make his own evaluation of the overall condition of the home, and is not intended to reflect the value of the premises, nor make any representation as to the advisability of purchase. The report expresses the personal opinions of the inspector, based upon his visual impressions of the conditions that existed at the time of the inspection only. The inspection and report are not intended to be technically exhaustive, or to imply that every component was inspected, or that every possible defect was discovered. No disassembly of equipment, opening of walls, moving of furniture, appliances or stored items, or excavation was performed. This inspection is a limited visual examination of the readily accessible systems and components of the home only.

This inspection is conducted in compliance with the standards of practice of the International Association of Certified Home Inspectors (Inter-NACHI), a copy of which is available at www.citywidehomeinspectors.com/sop.

Systems and conditions which are not within the scope of the building inspection include, but are not limited to: pools spas or their related equipment, formaldehyde, lead paint, asbestos, toxic or flammable materials, and other environmental hazards; pest infestation, playground equipment, efficiency measurement of insulation or heating and cooling equipment, internal or underground drainage or plumbing, any systems which are shut down or otherwise secured; water wells (water quality and quantity) zoning ordinances; intercom; security systems; heat sensors; central vacuum systems, cosmetics or building code conformity. Any general comments about these systems and conditions are informational only and are not within the scope of this inspection.

The inspection report should not be construed as a compliance inspection of any governmental or non-governmental codes or regulations. The report is not intended to be a warranty or guarantee of the present or future adequacy or performance of the structure, its systems, or their component parts. This report does not constitute any express or implied warranty of merchantability or fitness for use regarding the condition of the property and it should not be relied upon as such. Any opinions expressed regarding adequacy, capacity, or expected life of components are general estimates based on information about similar components and occasional wide variations are to be expected between such estimates and actual experience. We recommend that any deficiencies noted in this report be repaired or corrected after consultation with reputable qualified contractors. It is suggested that more than one quote be obtained before commencing with repairs.

The sellers' property information sheet (SPIS) may be referred to in this document. This item is a statement that is often completed by the seller regarding the condition of the subject property. The buyer is urged to obtain and review this document, if available, as it contains crucial information. Photographs, taken at the time of this inspection, are to be considered part of this inspection report.

We certify that our inspectors have no interest, present or contemplated, in this property or its improvement and no involvement with tradespeople or benefits derived from any sales or improvements. To the best of our knowledge and belief, all statements and information in this report are true and correct.

We assume no liability for the cost of repair or replacement of unreported defects or deficiencies either current or arising in the future. You agree that in all cases our liability shall be limited to liquidated damages in an amount not greater than the fee you paid us. You waive any claim for consequential, exemplary, special or incidental damages or for the loss of the use of the home/building. You acknowledge that the liquidated damages are not a penalty, but that we intend them to (i) reflect the fact that actual damages may be difficult and impractical to ascertain; (ii) allocate risk between us; and (iii) enable us to perform the inspection for the agreed upon fee.

Should any disagreement or dispute arise as a result of this inspection or report, it shall be decided by arbitration and shall be submitted for binding, non-appealable arbitration unless the parties mutually agree otherwise. In the event of a claim, the Client will allow City Wide Home Inspectors to inspect the claim prior to any repairs or waive the right to make the claim. Client agrees not to disturb or repair or have repaired anything which may constitute evidence relating to the complaint, except in the case of an emergency.

Report Table of Contents

BUILDING DATA	3
REPORT LIMITATIONS	4
SUMMARY*	6
GROUNDS	
ROOF COVERING	
CHIMNEY / GUTTERS / SIDING / TRIM	
EXTERIOR / ELECTRICAL / AC / GARAGE	10
KITCHEN	11
LAUNDRY	11
BATHROOMS	
INTERIOR ROOMS	
WINDOWS / FIREPLACES / ATTIC	19
BASEMENT	20
PLUMBING	21
HEATING SYSTEM	22
COOLING SYSTEM	23
ELECTRICAL	23
PHOTO GALLERY	24
GENERAL REMARKS	27
HOME MAINTENANCE SCHEDULE	39



ITEMS NOT OPERATING

None

MAJOR CONCERNS

None

POTENTIAL SAFETY HAZARDS

None

DEFERRED COST ITEMS

Items that have reached or are reaching their normal life expectancy or show indications that they may require repair or replacement <u>anytime during the next five (5) years.</u>

A/C unit older than 13 years Furnace older than 13 yrs

DEFINITIONS

SATISFACTORY (Sat.) - Indicates the component is functionally consistent with its original purpose but may show signs of normal wear and tear and deterioration.

MARGINAL(Marg.) - Indicates the component will probably require repair or replacement anytime within five years.

POOR - Indicates the component will need repair or replacement now or in the very near future.

MAJOR CONCERNS - A system or component that is considered significantly deficient or is unsafe.

SAFETY HAZARD - Denotes a condition that is unsafe and in need of prompt attention.

^{*} Items listed in this report may inadvertently have been left off the Summary Sheet. Customer should read the entire report, including the Remarks.

GROUNDS

		01100111		
Service Walks		☑ None	☐ Public sidewalk	needs repair
	☐ Concrete	☐ Flagstone	☐ Brick	☐ Other
Condition:	☐ Satisfactory	☐ Marginal	□ Poor	☐ Trip Hazard
	☐ Pitched towards hom	e ☐ Settling cracks	☐ Not visible	
Driveway		□ None		
Directia	☐ Concrete ☑ Asp		□ Pavers □ Other	
Condition:	✓ Satisfactory	☐ Marginal	□ Poor	☐ Trip hazard
Condition	☐ Fill cracks and seal		me ☐ Settling cracks	□ Not visible
Detic/Lensi				
Patio/Lanai		□ None	1	□ O(1 · · ·
C I''		Flagstone		□ Other
Condition:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Trip Hazard ☐ Not visible
	☐ Pitched towards hom	e (See Kemarks page)	☐ Settling cracks	☐ NOT VISIBLE
Deck		☑ None □ W	ood □ Composite	☐ Other
	☐ Treated	☐ Painted/Stained	☐ Railing/balusters	
Condition:	☐ Satisfactory	☐ Marginal	□ Poor	☐ Not visible
Deck/Patio/Por	ch Covers	☑ None □ Ea	arth to wood contact	Moisture/insect damage
Lacks:	☐ Metal straps/bolts/na:		proper attachment to house	_
		-	· -	
Porch (covered		☑ None	☐ Railing/baluste	
Support Pier:	□ Wood	☐ Concrete	☐ Other	☐ Not visible
Condition:	☐ Satisfactory	☐ Marginal	□ Poor	□ 6-6-4 H1
Floor:	☐ Satisfactory	☐ Marginal	□ Poor	☐ Safety Hazard
Balcony (2nd f	loor platform)	☑ None □ W	ood □ Metal	☐ Other
Railing:	☐ Yes	□ No	☐ Railing/balusters	recommended
Condition:	☐ Satisfactory	☐ Marginal	□ Poor	☐ Safety Hazard
Stoops/Steps		□ None	☐ Uneven risers	☐ Safety Hazard
0.000 0.000	☑ Concrete	□ Wood		Railing recommended
Condition:	☑ Satisfactory	☐ Marginal		Recommend baluster
	☐ Cracked	☐ Settled	☐ Damaged wood	
Fencing		□ None	☐ Type:	✓ Not evaluated
1 ending		□ Nolle	□ туре.	E Not evaluated
Landscaping A	ffecting Foundation	(See Remarks page)		
Negative grade at		□ North □ South	☑ Satisfactory	
- 1-8 8	☐ Recommend addition		☐ Recommend wind	low wells/covers
	☐ Trim back trees/shrul		☐ Wood in contact/t	
	☐ Yard drains observed		□ N/A	
Detaining Wall		□ Yes	□ Na	
Retaining Wall	☐ Concrete	□ Wood	☑ No	Cofoty Hogand
Visual Condition				Safety Hazard
Visual Condition:	□ Satisfactory	☐ Marginal	□ Poor	
Hose Bibs		☑ Yes		No anti-siphon valve
Operates:	☑ Yes	□ No	\square Not tested \square	Not on
General Comm	nents			
30		l		

Fencing is not part of a home inspection. General site drainage was properly sloping away from the house. Maintain a positive drainage slope away from the foundation.

ROOF COVERING

General Inform	nation						
Roof Visibility		All					
Inspected From	n	Ground with b	oinoculars				
Style of Roof							
~ I	oination: ☐ Gable ☐ Low	☑ Hip □ Medium	☐ Mansard☑ Steep	☐ Shed ☐ F	Flat	ſ	
Roof Covering							
Type: Asphalt	Estimated Laye	ers: 1 layer	Approx	imate age of cover:	1 to 5 yrs		
Ventilation Sys	stem						
Combination:	☑ Soffit	☐ Ridge		☐ Gable	☑ Roof		
	□ Powered	☐ Eaves		☐ Other			
Flashing Mate	rial						
Combination:	☑ Galv./Aluminum	☐ Asphalt	☐ Lea	d □ Rubb	er □ Not v	risible	
	□ Copper	☐ Other					
Valley Material							
Combination:	☑ Galv./Aluminum	☐ Asphalt		□ Copper	□ N/A		
	☐ Not visible	☐ Other					
	dition of the Following a						
Roof Covering		☑ Satisfact	tory	☐ Marginal	☐ Poo	r	
Condition:	☐ Curling ☐ Moss Buildup	☐ Cupping	•	☐ Missing tabs/sh	_	tiles □ Burn Spots	
	☐ Exposed Felt	☐ Nail Popp☐ Other	oing	☐ Ponding	⊔ Burn	Spots	
Mandladan	Exposed Felt		1 \	(G 1			
Ventilation		(See Rema	rks page)	(See Attic page)			
Flashings		☐ Not visi	ble	atisfactory \Box	Marginal [□ Poor	
	☐ Rusted	□ Recomm	end Sealing	☐ Pulled away fro	om chimney/roof		
Valleys		☑ Satisfact	tory	☐ Marginal	□ Poo	r	
	☐ Not visible	□ N/A	10 1	☐ Rusted			
	□ Holes	□ Recomm	end Sealing				
Skylights		□ Yes	☑ No	☐ Satisfactory	☐ Marginal	□ Poor	
Plumbing Ven	ts	☑ Yes	□ No	☑ Satisfactory	☐ Marginal	□ Poor	
General Comn	nents						
	·						

Roof covering appeared in overall satisfactory condition at the time of the inspection.

CHIMNEY / GUTTERS / SIDING / TRIM

		- /		_110 /	OIDII		X11V1
Chimney(s)			✓ None	Location	(s):		
Viewed from:	□ Roof		☐ Ladder at			d w/binoculars	
Chase:		Stone	☐ Metal	☐ Fran		Blocks	☐ Stucco
	Evidence of:		cked chimney		se mortar jo		☐ Loose brick
			es in metal	☐ Rust		Flaking	
Flue:	☐ Tile			☐ Unlined		Not visible	
	Evidence of:	□ Sca		☐ Cracks		Creosote	
			ve flue(s) cleaned				See Remarks page)
☐ Recommend c	cricket/saddle flash	ning		☐ Spark arr	restor/rain c	ap recommende	ed
Gutters & Dow	nspouts/		□ None	(See Ren	narks page	e)	
☐ Insides need to	o be cleaned		☐ Ponding				
	☑ Galvanized/A	lum.	☐ Copper		□ Vinyl		☐ Other
Condition:	☑ Satisfactory		☐ Marginal		□ Poor		☐ Rusting
	☐ Hole in main	run		Leaking:	☐ Corner	's	☐ Joints
Extension needed:	□ North		☐ South		☐ East		□ West
Siding							
Material:	Brick & Stucco						
Condition:	☑ Satisfactory		☐ Marginal	□ Poor	. 🗆	Recommend r	epair/painting
Window Frame	es						
Material:	Vinyl	•					
Condition:	☑ Satisfactory		☐ Marginal		□ Poor		
	☐ Recommend p	painting	5	□ Dan	naged wood	i	
Trim, Soffit, Fa	ascia						
Trim Material:	Metal	•	Condition: S	atisfactory			
Soffit Material:	Metal		Condition: S	Satisfactory			
Fascia Material:	Metal		Condition: S	atisfactory			
Caulking							
Condition:	☑ Satisfactory		☐ Marginal		□ Poor		
	☐ Recommend a	round v		/masonry led	ges/corners	/utility penetrat	ions
General Comn	nents						

Gutters were in overall adequate condition. Siding appeared to be in overall adequate condition. Trim appeared to be intact and in overall maintained condition.

EXTERIOR / ELECTRICAL / AC / GARAGE

Exterior Wall C	onstruction							
Construction Style		☑ Satisf	factory \square N	Marginal	□ Poor			
Exterior Doors			☑ Entra	nce (1);	Storm (2)	; Patio (3)		
Weather stripping:	☑ Satisfactory	<u>.</u>	☐ Margir	nal		l Poor		
Condition:	☑ Satisfactory		☐ Margir			l Poor		
Exterior Electri	cal Service							
	☐ Overhead	☑ Uno	derground	Servic	e drop:	☐ Satis:	factory	☐ Needs service
Exterior outlets:		□ No	8	Opera	-	☑ Yes	J	□ No
GFCI protected:		□ No		Opera		☑ Yes		□No
Reverse polarity:		☑ No			ground:	☐ Yes		☑ No
Overhead wires:			nan 1 meter f			window 🗆 E	Extension of	cord/exposed Romex
Potential safety		□ Yes		☑ No		See Remarks		
A/C Condenser/	Heat Pump		□ None	Approxi	mate age:	15 to 20 yrs		
#1 Brand: Nordy				••	Ü	·		Shutoff: No
Condition:	☑ Satisfactory	□ Ma	rginal [□ Poor	□ Rus	sted/dirty	Level: ✓	ĭ Yes □ No
Garage								
Garage Type:	Attached	Garag	ge Size: Do	uble Car				
Automatic open	er: Yes	Opera	tional: Yes					
Safety reverse: I	Present: 🗹 Yes	□No	Operates:	☐ Yes	□ No	☑ Needs ad	ljusting	□Safety Hazard
Electric sensor:	Present: ✓ Yes	□ No	Operates:		□ No	☐ Too low	·	□Safety Hazard
Roofing:	☑ Same as house	•	Condition	ı:	✓ Satis	factory \square	Marginal	□ Poor
Floor:	Concrete		☐ Gravel			l Asphalt	•	☐ Dirt
	Burners less than	45 cm a	bove garage	floor: ✓	1 N/A □	l Yes 🗆	No $\square S$	afety hazard
	Condition:		isfactory			ks 🗆 Large	e settling c	racks
Overhead door:	□ Wood	☐ Fib	erglass	□ Ma	sonite	☑ Meta	.1	☐ Other
	Condition:	☑ Sat	isfactory	□ Ma	rginal	☐ Poor	□ Rep	air, replace, paint
Service door:	☑ Satisfactory	□ Ma	rginal	□ Poo		☐ None		, . , .
Sill plates:	☐ Elevated	☐ Flo	or level	☐ Bot	th	☑ Not v	visible	☐ Rotted
Electricity prese	nt: ☑ Yes	□ No	GFCI Pr	otected:	☐ Yes	☑ No	Operates:	☑ Yes □ No
	Reverse polarity/o	pen gro	ound: 🗆 Yes	s □ Saf	ety Haza	rd 🗹 No	☐ Hand	yman/ext. cord wiring
Firewall:	(Between garage	& livin	ig area) [□ N/A	✓	Present	☐ Missi	ng 🗆 Damaged
Fire door:	☐ Not verifiable	☐ Not	a fire door	□ Nee	eds repair	✓ Satis	factory	-
Auto closure:	□ N/A	☑ Sat	isfactory		☐ Inop	erative \square	Missing	☐ Needs repair
General Comm	nonto							

Doors were reviewed and found to be in working order. Lights appeared to be in normal condition: not all lights were tested. Exterior outlets tested were in normal working order.

KITCHEN

Countertops		☑ Satisf	factory	□M	arginal	□ Poor		
0-11								
Cabinets Condition:	☑ Satisfactory		☐ Margir	na1	□ Poo	or □ D oo	commend r	anaire
-	•		— Wangii	141		л 🗀 Кс		cpans
Plumbing Con		DIN.		Din 11-/		□ V.s.	DIN.	
Faucet leaks: Drainage:	☐ Yes☑ Adequate	☑ No □ Poo	n r	Pipes leak/corro Water pressure:		☐ Yes ☐ Adequate	☑ No □ Poor	
		100	<i>)</i> 1	water pressure.		- Adequate	□ 1 001	
Walls & Ceiling								. •
Condition	☑ Satisfactory	□ Ma	rginal	□ Poor		☐ Typical cracks	☐ Moistı	ire stains
Heat Source P	resent		☑ Yes	□ No				
Floor	Z Catiafaatam	□Ма		□ D		□ C1:	□ C	l
Condition	☑ Satisfactory	□ Ma	rginai	□ Poor		□ Sloping		KS
Appliances			(See Re	marks page)				
Dishwasher:	☑ Yes	□ No		Operates:		☑ Yes	□ No	□ N/A
Range:	☑ Yes	□ No		Operates:		☑ Yes	□ No	□ N/A
Oven:	☑ Yes	□ No		Operates:		☑ Yes	□ No	□ N/A
Exhaust fan:	☑ Yes	□ No		Operates:		☑ Yes	□ No	□ N/A
Refrigerator:	☑ Yes	□ No		Operates:		☑ Yes	□ No	□ N/A
Other:	□ Yes	□ No		Operates:		☐ Yes	□ No	□ N/A
Electrical								
Outlets present:	☑ Yes	□ No		Operates:		☑ Yes	□ No	
GFCI protected:		☑ No		Operates:		☐ Yes	□ No (R	emarks)
Open ground/rev	erse polarity with	in 1 me	ter of water:	\square Yes \square S	Safety H	l azard ☑ No		
General Comm	nents:							
G 1	1 01:	. 1	1	TD1	,		1 . 1 1	1
						le active piping or		
						except as noted.		
	tripping from occ		iouid de take	en not to operate	z majo	r counter appliance	es at the san	ie time to
prevent nuisance	urpping from occ	uiiiig.						
			LA	UNDRY				
Room Compoi	nents							
Laundry sink:	□ N/A	Fauce	leaks:	□ Yes •	ĭ No	Pipe leaks:	☐ Yes	☑ No
Cross connection	ıs: □ Yes	☑ No	ne apparent	Heat source	present	: ☑ Yes	□ Not V	isible
Room appears ve	ented:	□ No						
Dryer vented:	□ N/A		☑ Wall	☐ Ceiling		☐ Not vented		
Electrical: Open g	ground/reverse pola	rity witl	nin 1 meter of	water: $\square Y \in$	es 🗆 S	afety Hazard	☑ No	
Appliances prese	nt: 🗹 Washer	ſ	☑ Dryer	☐ Water hea	ater	☐ Furnace	☐ Other	
Gas pipe:	☑ N/A	Valve	shutoff:	□ Yes □	□No	☐ Cap Needed	☐ Safety	Hazard
General Comm	nents							

At the time of the inspection the laundry facilities were in satisfactory condition.

BATHROOMS

Bath: Primary I	3edroom					
Sinks	Faucet leaks:	☐ Yes	☑ No		Pipes leak:	□ Yes ☑ No
Tubs	Faucet leaks:	□ Yes	☑ No		Pipes leak:	☐ Yes ☑ No
Showers	Faucet leaks:	□ Yes	☑ No		Pipes leak:	☐ Yes ☑ No
Toilet:	Bowl loose	□ Yes	☑ No	<i>Operates</i> : ✓ Yes	□ No □ Cracked b	
Whirlpool:	Bowrioose	□ Yes	☑ No	Operates: ☐ Yes	□ No	owi = ronet leans
Shower/Tub area		☑ Cerami		☐ Fiberglass	☐ Masonite	☐ Other
Shower Tub area	Condition:	✓ Satisfac		☐ Marginal	□ Poor	☐ Rotted floors
	Caulk/Grouting r		☐ Yes	☑ No	Where:	Li Rotted Hoors
Drainage:	✓ Satisfactory	recueu.	☐ Margin		□ Poor	
Water flow:	✓ Satisfactory		□ Margin		□ Poor	
Moisture stains p	•	□ Walls	_		□ 1 001	
-				ted: ☑ Yes □ No	Operates: ☑ Y	as DNo
Outlets present.	Open ground/rev				☐ Yes ☐ No	CS LINO
	Potential safety				e Remarks page)	
Uast source press	<u> </u>	Yes	esent.		e Kemarks page)	
Heat source prese Exhaust fan:)navatas:	☑ Yes	□ No □ Noisy	7
Windows:			Operates:		-	
				lass □ None □ Ev Does not latch □ H		
Door:	☑ Sat. ☐ Marg.	□ P001 L	ı noies 🗆	Does not laten \Box F	iardware broken \square	None
General Comm	ents					
noted.	Jua ana Finantia					
Bath: Joint Bed			-		7 2	
Sinks	Faucet leaks:	□ Yes	☑ No		Pipes leak:	☐ Yes ☑ No
Tubs	Faucet leaks:	□ Yes	☑ No		Pipes leak:	☐ Yes ☑ No
Showers	Faucet leaks:	□ Yes	☑ No		Pipes leak:	☐ Yes ☑ No
Toilet:	Bowl loose	□ Yes	☑ No	<i>Operates</i> : ✓ Yes	□ No □ Cracked b	owl ☐ Toilet leaks
Whirlpool:		□ Yes	☑ No	<i>Operates</i> : □ Yes	□ No	
Shower/Tub area		☑ Cerami		☐ Fiberglass	☐ Masonite	Other
	Condition:	☑ Satisfac		☐ Marginal	Poor	☐ Rotted floors
	Caulk/Grouting r	needed:	□ Yes	☑ No	Where:	
Drainage:	☑ Satisfactory		☐ Margin		Poor	
Water flow:	✓ Satisfactory		☐ Margin		□ Poor	
Moisture stains pr		□ Walls				
Outlets present:				ted: ☑ Yes □ No		es ⊔ No
	Open ground/rev				☐ Yes ☑ No	
**	Potential safety		esent:	☐ Yes ☑ No (See	e Remarks page)	
Heat source prese		Yes		□ No		
Exhaust fan:			Operates:	☑ Yes	□ No □ Noisy	
Windows:	La Cat I Name	1 1 1) 0 0 0 0	I Crooked a	1 I I N I I I T	dance of leaking inc	
				lass ☐ None ☐ Evi		
Door:				Does not latch \square H		

At the time of the inspection, the bathroom and its components were found to be in satisfactory condition except as noted.

Bath: Bedroom	n Ensuite							
Sinks	Faucet leaks:	☐ Yes	☑ No			Pipes leak:	□ Yes 5	₫ No
Tubs	Faucet leaks:	☐ Yes	☑ No			Pipes leak:	□ Yes 5	₫ No
Showers	Faucet leaks:	☐ Yes	☑ No			Pipes leak:	□ Yes 5	
Toilet:	Bowl loose	☐ Yes	☑ No	Operates:	☑ Yes	☐ No ☐ Cracked b	owl 🗆 Toil	et leaks
Whirlpool:		☐ Yes	☑ No	Operates:		□ No		
Shower/Tub area:		☑ Cerami		☐ Fibergla		☐ Masonite	☐ Other	
	Condition:	☑ Satisfa		☐ Margina	1	□ Poor	☐ Rotted	floors
	Caulk/Grouting r	reeded:	☐ Yes	☑ No		Where:		
Drainage:	☑ Satisfactory		☐ Margin			□ Poor		
Water flow:	☑ Satisfactory		☐ Margin			□ Poor		
Moisture stains p			☐ Ceiling	•				
Outlets present:				eted: 🗹 Yes		•	es □ No	
	Open ground/rev					☐ Yes ☑ No		
	Potential safety	_	resent:	☐ Yes ☑ N	lo (Se	e Remarks page)		
Heat source prese		Yes		□ No				
Exhaust fan:			Operates:	☑ Yes		□ No □ Nois		
Windows:						idence of leaking ins		S
Door:	☑ Sat. ☐ Marg.	□ Poor L	⊔ Holes ⊔	Does not late	ch ⊔ F	Hardware broken □	J None	
General Comm	ents							
	e inspection, the ba	athroom an	d its compo	onents were f	ound to	be in satisfactory co	ondition exc	ept as
noted.								
Dad. Main da								
Bath: Main floo		☐ Yes	☑ No			Din 1 1	□ V □	71 N.
Sinks Toilet:	Faucet leaks: Bowl loose	□ Yes	⊻ No ☑ No	Omanatası	□ Vac	Pipes leak: ☐ No ☐ Cracked b	☐ Yes ☐	
		□ res			v ies	□ Poor	owi 🗀 ioii	et leaks
Drainage: Water flow:	✓ Satisfactory ✓ Satisfactory		☐ Margin☐ Margin			□ Poor		
	•	□ W ₀ 11 ₀	☐ Margin			□ P00F		
Moisture stains pr		☐ Walls	_		□ No	Onanataa	☑ Yes	□ No
Outlets present:	☑ Yes ☐ No Open ground/rev	GFCI pro			□ No □ Yes	<i>Operates</i> : ☑ No	<u>v</u> ies	□ No
	Potential safety				□ res ☑ No	(See Remarks pag	-o)	
Heat source prese	•	Mazarus pr ✓ Yes	resent:	□ No	M INO	(See Kemarks pag	ge)	
Exhaust fan:			Operates:	☐ No ☐ Yes		□ No □ Nois	V	
Windows:					- □ Evi	dence of leaking ins		
Door:						Hardware broken		
General Comm	ents							

At the time of the inspection, the bathroom and its components were found to be in satisfactory condition except as noted.

Bath: Basemer	nt					
Sinks	Faucet leaks:	☐ Yes	☑ No		Pipes leak:	☐ Yes ☑ No
Showers	Faucet leaks:	☐ Yes	☑ No		Pipes leak:	☐ Yes ☑ No
Toilet:	Bowl loose	☐ Yes	☑ No	<i>Operates</i> : ✓ Yes	☐ No ☐ Cracked b	owl ☐ Toilet leaks
Shower area:	☑ Ceramic/Plast	ic	☐ Fiberglass		☐ Masonite	☐ Other
	Condition:	✓ Satisfact	ctory	☐ Marginal	□ Poor	☐ Rotted floors
	Caulk/Grouting	needed:	☐ Yes	☑ No	Where:	
Drainage:	☑ Satisfactory		☐ Margin	□ Poor		
Water flow:	☑ Satisfactory		☐ Margin	al	□ Poor	
Moisture stains p	resent:	\square Walls	☐ Ceiling	s ☑ No		
Outlets present:	☑ Yes □	No C	GFCI protec	ted: ☑ Yes ☐ No	Operates: ☑ Y	es □ No
	Open ground/rev	erse polarit	y within 1 r	neter of water:	□ Yes ☑ No	
	Potential safety	hazards pi	resent:	☐ Yes ☑ No (Se	e Remarks page)	
Heat source prese	ent:	Yes		□ No		
Exhaust fan:	☑ Yes □	No C	Operates:	☑ Yes	□ No □ Nois	y
Windows:	☐ Sat. ☐ Marg.	□ Poor □	Cracked g	lass ☑ None □ Ev	idence of leaking ins	ulated glass
Door:	☑ Sat. ☐ Marg.	□ Poor □	☐ Holes ☐	Does not latch □ I	Hardware broken	None
General Comm	nents					

At the time of the inspection, the bathroom and its components were found to be in satisfactory condition except as noted.

INTERIOR ROOMS **PRIMARY BEDROOM Location:** Second floor Walls & Ceiling: ✓ Satisfactory □ Poor ☐ Marginal ☐ Typical Cracks ☐ Holes Moisture stains: \square Yes ☑ No Flooring: ✓ Satisfactory ☐ Marginal ☐ Poor ☐ Squeaks □ Slopes Ceiling fan: \square N/A ☑ Satisfactory ☐ Marginal □ Poor Electrical: Switches: ✓ Yes No Outlets: ☑ Yes □ No ☑ Yes □ No Operates: Open ground/reverse polarity: □Yes ☐ Safety Hazard ☑ No ☐ Covers missing □ Not visible ✓ Yes Heat source present: ☑ Sat. ☐ Marg. ☐ Poor ☐ Cracked glass ☐ None ☐ Evidence of leaking insulated glass Windows: ☑ Sat. ☐ Marg. ☐ Poor ☐ Holes ☐ Does not latch ☐ Hardware broken ☐ None Door: ☑ Sat. ☐ Marg. ☐ Poor ☐ Holes ☐ Missing ☐ Tracks broken ☐ None Closet Doors: **General Comments:** At the time of the inspection the room was found to be in overall satisfactory condition. **BEDROOM #2 Location:** Second floor Walls & Ceiling: ✓ Satisfactory ☐ Marginal ☐ Poor ☐ Typical Cracks ☐ Holes ☑ No Moisture stains: \square Yes ☐ Marginal □ Poor Flooring: ✓ Satisfactory ☐ Squeaks □ Slopes Ceiling fan: □ N/A ☑ Satisfactory ☐ Marginal □ Poor Electrical: Switches: ✓ Yes No Outlets: ☑ Yes □ No Operates: ☑ Yes □ No Open ground/reverse polarity: ☐ Yes ☐ Safety Hazard ☑ No ☐ Covers missing Heat source present: ✓ Yes ☐ Not visible Windows: ☑ Sat. ☐ Marg. ☐ Poor ☐ Cracked glass ☐ None ☐ Evidence of leaking insulated glass ☑ Sat. ☐ Marg. ☐ Poor ☐ Holes ☐ Does not latch ☐ Hardware broken ☐ None Door: Closet Doors: ☑ Sat. ☐ Marg. ☐ Poor ☐ Holes ☐ Missing ☐ Tracks broken ☐ None General Comments: At the time of the inspection the room was found to be in overall satisfactory condition. **BEDROOM #3**

Location: Seco	nd floor								
Walls & Ceiling:	☑ Satisface	tory	\square M	arginal		□ Poor	☐ Typical	Cracks	☐ Holes
	Moisture s	tains:	□ Ye	es		☑ No			
Flooring:	☑ Satisface	tory	\square M	☐ Marginal		□ Poor	☐ Squeaks ☐ Slop		☐ Slopes
Ceiling fan:	\square N/A	-	☑ Sa	tisfactory		☐ Marginal	_	□ Poor	
Electrical:	Switches:	✓ Yes	□ No	Outlets:	✓ Yes	□ No	Operates:	✓ Yes	□ No
	Open grou	nd/reverse	polarity:	☐ Yes	☐ Safet	y Hazard	☑ No	□ Cove	ers missing
Heat source prese	ent: 🗹	Yes \square	Not visible						
Windows:	☑ Sat. □	Marg. □	Poor \square Cr	acked glass	☐ None	☐ Evidence of	f leaking insi	ulated gla	ass
Door:	☑ Sat. □	Marg. □	Poor 🗆 Ho	oles 🗆 Doe	s not late	h 🛮 Hardwar	e broken 🗆	l None	
Closet Doors:	☑ Sat. □	Marg. □	Poor He	oles \square Mis	sing 🗆 🗆	Tracks broken	□ None		
General Comm	nents:								

BEDROOM #4	4						
Location: Seco	ond floor						
Walls & Ceiling:	☑ Satisfactory	☐ Marginal		□ Poor	☐ Typical (Cracks	☐ Holes
	Moisture stains:	□ Yes		☑ No	• •		
Flooring:	☑ Satisfactory	☐ Marginal		□ Poor	☐ Squeaks		☐ Slopes
Ceiling fan:	□ N/A	☑ Satisfactory		☐ Marginal	_	□ Poor	_
Electrical:	Switches: ✓ Yes ✓		✓ Yes	□ No	Operates:	✓ Yes	□ No
	Open ground/reverse pol	larity: □ Yes	☐ Safet	y Hazard	☑ No	□ Cove	rs missing
Heat source prese		t visible					
Windows:	☑ Sat. ☐ Marg. ☐ Poo						SS
Door:	☑ Sat. ☐ Marg. ☐ Poo					None	
Closet Doors:	☑ Sat. ☐ Marg. ☐ Poo	or \square Holes \square Miss	sing 🗆 T	Tracks broken	□ None		
General Comm	ents:						
A 1		6 1, 1	11 6	11.11			
At the time of the	e inspection the room was	s found to be in over	all satisfa	actory conditio	on.		
LIVING BOOK	. .						
LIVING ROOI							
Location: First							
Walls & Ceiling:	•	☐ Marginal		Poor	☐ Typical (Cracks	☐ Holes
	Moisture stains:	□ Yes		☑ No			_
Flooring:	☑ Satisfactory	☐ Marginal		Poor	☐ Squeaks		\square Slopes
Ceiling fan:	☑ N/A	☐ Satisfactory	_	☐ Marginal		□ Poor	_
Electrical:	Switches:		☑ Yes		Operates:	☑ Yes	
	Open ground/reverse pol		☐ Safety	y Hazard	☑ No	□ Cove	rs missing
	ent: Yes Not vis						
Windows:	☑ Sat. ☐ Marg. ☐ Poo						
Door:	□ Sat. □ Marg. □ Poo	or ⊔ Holes ⊔ Does	s not latel	h ⊔ Hardwar	e broken ⊻	None	
General Comm	ents:						
At the time of the	e inspection the room was	found to be in over	all satisfa	actory conditio	n.		
	1			•			
DINING ROO	М						
Location: First							
Walls & Ceiling:		☐ Marginal		□ Poor	☐ Typical (Cracks	☐ Holes
wans & cennig.	Moisture stains:	□ Yes		☑ No	ш тургеш ч	Clacks	L Holes
Flooring:	✓ Satisfactory	☐ Marginal		□ Poor	☐ Squeaks		☐ Slopes
Ceiling fan:	☑ N/A	☐ Satisfactory		☐ Marginal	— Бересика	□ Poor	□ blopes
Electrical:	Switches: Yes :		☑ Yes	□ No	Operates:	✓ Yes	П №
Licetrical.	Open ground/reverse pol			y Hazard	Ø No		rs missing
Heat source prese			□ baici,	y 11azai u	E 110		13 1111331115
Windows:	☑ Sat. ☐ Marg. ☐ Poo		□ Fvid	ence of leaking	o insulated o	lace	
Door:	□ Sat. □ Marg. □ Poo						
i 					oronon L		
General Comm	ents:						
A. d. d. C.d.		6 1 1	11 6				

EATING AREA

Location: First	floor									
Walls & Ceiling:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Typical (Cracks	☐ Holes				
	Moisture stains:	□ Yes	☑ No							
Flooring:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Squeaks		☐ Slopes				
Ceiling fan:	☑ N/A	□ Satisfactory	☐ Marginal		□ Poor					
Electrical:	Switches: ✓ Yes ☐	No Outlets:	☑ Yes □ No	Operates:		□ No				
	Open ground/reverse po		☐ Safety Hazard	☑ No	☐ Cove	rs missing				
Heat source present: ☑ Yes ☐ Not visible										
Windows:	☑ Sat. ☐ Marg. ☐ Po									
Door:	☑ Sat. ☐ Marg. ☐ Po	or □ Holes □ Doe	es not latch	re broken ⊻	1 None					
General Comments:										
At the time of the OFFICE	At the time of the inspection the room was found to be in overall satisfactory condition. OFFICE									
Location: First	floor									
Walls & Ceiling:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Typical (Cracks	☐ Holes				
	Moisture stains:	□ Yes	☑ No							
Flooring:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Squeaks		☐ Slopes				
Ceiling fan:	☑ N/A	□ Satisfactory	☐ Marginal		□ Poor					
Electrical:	Switches: ✓ Yes ☐	No Outlets:	☑ Yes □ No	Operates:	✓ Yes	□ No				
	Open ground/reverse po	larity: □Yes	☐ Safety Hazard	☑ No	☐ Cove	rs missing				
Heat source prese	ent: ☑ Yes ☐ Not vi	sible								
Windows:	☑ Sat. ☐ Marg. ☐ Po	or \square Cracked glass	□ Evidence of leaking	g insulated gl	lass					
Door:	☑ Sat. ☐ Marg. ☐ Po	or □ Holes □ Doe	es not latch	re broken ✓	1 None					
General Comm	ents:									

REC ROOM

Location: Baser	ment					
Walls & Ceiling:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Typical (Cracks	☐ Holes
	Moisture stains:	□ Yes	☑ No			
Flooring:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Squeaks		☐ Slopes
Ceiling fan:	☑ N/A	□ Satisfactory	☐ Marginal		□ Poor	
Electrical:	Switches: ✓ Yes ☐	No Outlets:	☑ Yes □ No	Operates:	✓ Yes	□ No
	Open ground/reverse po		☐ Safety Hazard	☑ No	□ Cove	rs missing
Heat source prese	ent: ☑ Yes ☐ Not vis	sible				
Windows:	☑ Sat. ☐ Marg. ☐ Po	or Cracked glass	☐ Evidence of leaking	g insulated gl	lass	
Door:	□ Sat. □ Marg. □ Po	or □ Holes □ Doe	es not latch	re broken ✓	1 None	
General Comm	ents:					
At the time of the BASEMENT F	inspection the room was	s found to be in over	all satisfactory condition	n.		
Location: Baser	nent					
Walls & Ceiling:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Typical (Cracks	☐ Holes
	Moisture stains:	☐ Yes	☑ No			
Flooring:	☑ Satisfactory	☐ Marginal	□ Poor	☐ Squeaks		\square Slopes
Ceiling fan:	☑ N/A	□ Satisfactory	☐ Marginal		□ Poor	
Electrical:	Switches: ✓ Yes ☐	No Outlets:	☑ Yes □ No	Operates:	☑ Yes	□ No
	Open ground/reverse po		☐ Safety Hazard	☑ No	□ Cove	rs missing
Heat source prese	ent: ☑ Yes ☐ Not vis	sible				
Door:	☑ Sat. ☐ Marg. ☐ Po	or □ Holes □ Doe	s not latch	re broken] None	
General Comm	ents:					

WINDOWS / FIREPLACES / ATTIC

		<i>-</i> /		711110
Interior Windows/Gla	ISS			
General condition:	☑ Satisfactor		al 🗆 Poor	☐ Painted shut
☐ Hardware missing	☐ Glazing co	ompound needed	☐ Cracked glass	☐ Broken counter-balance mech.
☐ Surface deterioration	: (See Remark	ks page)	☑ Representative n	number of windows operated
Fireplace		□None Lo	ocation(s): Living ro	oom
☑ Gas	□ Wood	□ Wood burner	stove (See Remark	cs page)
☐ Masonry ins			•	• 0
☐ Blower built			□ Damper	r operates \Box Damper missing
☐ Open joints or cracks				ricated panels damaged/worn
Hearth: Satisfactory		□ No	Mantle:	✓ Satisfactory ☐ Loose
☐ Recommend having		re-examined	□ Vent le	•
_	, 			1
Stairs	□ (C ('. C	✓ Satisfactory	☐ Margi	
Handrail:	✓ Satisfactor			☐ Safety Hazard
Risers/Treads:	☑ Satisfactor	ry	al 🗆 Poor	☐ Risers/treads uneven
Smoke/CO Detectors	i	(See Remarks)	page)	
Present:				
				ired on all levels of a home with sleeping
every 5 yrs and most hardwir				st battery operated units should be replaced
Attic		,		
Access: Access panel	Access Location	: Bedroom closet	Inspected from:	Access nanel
	Complete	☐ Partial	✓ None	recess paner
	ose fill fiberglass			R Rating: R32 Standard
	alled in:	_	□ Walls	□ Not Visible
			nostat controlled	
	isfactory			- Surety Huzuru
	oden trusses			
	wood			
Roof Sheathing Conditi		v □ Marginal □ P	oor 🗆 Rotted 🗆	Stained Delaminated
	tic: □ Yes ☑ No			ble □ N/A (See Remarks page)
Chimney chase:				1 0 /
Structural problems obs	erved: \square Yes	⊠ No □ See c	omments below	
	Not visible	☐ Improperly ins	talled	
-	Kraft faced	☐ Plastic	(See Remarks pag	e)
Electrical:	Open junction box	es) \square Hand	yman wiring	☐ Visible knob-and-tube
General Comments				
-				

Rafters / Trusses showed no major defects or damage at the time of inspection. Roof sheathing, examined from the attic, showed no major defects or moisture damage. Insulation level is normal for the age of the home. Ventilation was normal.

BASEMENT

(See Remarks page)

Stairs					
Condition:	☑ Satisfactor		☐ Marginal	□ Poor	☐ Safety Hazard
Handrail: ☑ Yes		ndition:	☑ Satisfactory	☐ Marginal	□ Poor
Headway over stairs:	☑ Satisfactor		☐ Marginal	□ Poor	
Under carriage:	☑ Satisfactor	ry	☐ Marginal	□ Poor	☐ Not visible
Foundation					
Wall Material:	Poured Conc	rete			
Condition:	Satisfactory				
Foundation Cracks:	□ Yes ☑ N	None Vis	ible Visib	le from: Exten	rior Interior
Movement apparent:	□ Yes ☑ N	lо			
Partially/Covered walls:	☑ Yes □ N	Vo			
	Condition re	eported :	above reflects <u>visib</u>	<u>le</u> portion only	
Floor			(See vapour bar	rier remarks)	
Material:	Concrete				
Condition:	Satisfactory				
Seismic Bolts			Not applicable		
			11		
Basement Drainage					
Indication of moisture:	No				
Sump Pump:	No St	ump Pun	np Operates: Not a	pplicable	
Floor drain(s) present:	Yes	•			
Drain Tile (See Remarks	nage)	□Р	almer valve present	☐ Not Visible	(See Remarks page)
2.6 (500 2.0	pge/		uniter varve present	_ 1,00 , 151016	(See Heller)
Girders (1), Columns (2)		□N	I/A		
	☑ Steel		□ Wood	□ Block	☐ Concrete ☐ Not visible
Condition:	☑ Satisfactor	ry	☐ Marginal	□ Poor	☐ Stained/rusted
Joists /Trusses					
☑ Joist ☐ Trusses	☐ I-Joist		☐ Steel	☑ Wood	□Concrete □ Not visible
	□ 2x6		☑ 2x8	□ 2x10	□ 2x12
Sub Floor					
	☐ Indication	of moist	ture stains/rotting		
				viewed from bas	sement or crawl space
General Comments	Г				
General Comments					

Foundation appeared to be in overall satisfactory condition. Foundation walls were covered/partially covered with paneling/drywall/insulation and were not visible. No representation can be made to the conditions of the covered/partially covered walls. Floor appeared to be in overall satisfactory condition. No active seepage visible at the time of the inspection. Thermal imaging scans of all the accessible basement exterior walls did not reveal any signs of moisture present. No representation can be made to future leaking of the basement walls.

PLUMBING

Water Service		Shut off location	: Basement		
Water entry piping: Co	pper Wat	er lines: Copper			
	Lead (other tha	n solder joints):	☐ Yes ☑ No	☐ Service entry	☐ Unknown
	Water flow:	Satisfactory	□ Poor	Cross connection:	\square Yes \square No
		Satisfactory	□ Poor □ Abo	ve 80 psi (Needs eva	luation)
	Pipes: ☐ Corre	oded Leaking	☐ Valves broke	n/missing	ssimilar metal
Drain/waste/vent pipe:	Plastic				
	Condition:	Satisfactory	☐ Marginal	□ Poor	☐ Not visible
	Waste discharge	e: ☑ Satisfactory	☐ Slow drain		
Gas Lines		☐ Not visible	☐ Shutoff miss	sing	
	☐ Copper	□ Brass	☑ Black iron	☐ Stainless steel	□ CSST
Water Heater					
Brand name: Rheem					
Energy Source: Gas	Approx. age	:6 yrs		Capacity: 50 gallo	n
Rental Unit: Yes		Seismic restraints	needed: ☑ N/A 🗆] Yes □ No	
Relief valve:	\square Yes \square N	o Extension p	roper: ☑ Yes	□ No □ Missi	ing
Vent pipe:	□ N/A ☑ Satis	sfactory Improper	pitch Rusted	☐ Safety Hazard	
Water Equipment		(Units not evalu	ated)		
Water Softener	□Yes ☑ N	o Plumbing ho	oked up: ☐ Yes	□No	
Whole Home Filter	□Yes ☑ N	o Plumbing ho	oked up: ☐ Yes	□No	
UV Filter	□Yes ☑ N	o Plumbing ho	oked up: ☐ Yes	□No	
General Comments					

Overall the plumbing system, faucets, water pressure and drain rates were found to be in satisfactory condition at the time of the inspections.

HEATING SYSTEM

Fuel Shutoff for	Duilding	Main fuel shutoff location: Outside at gas meter				
ruei Siluloii ioi	bullaling	Main ruer s	muton location: Outside	e at gas me	etei	
Forced Air Syste	em	☑ Central	Unit □ Wall	Furnace	☐ Floor Furnace	_
	Brand name: Go	odman		Approximate age: 15 to 20 yrs		
Energy source: (Gas Furna	ce Efficiency:	: High Efficiency		•	
Hot air systems: 1	Direct drive					
Heat exchanger:	Sealed unit, not visible	View is ex	ktremely limited - See	Remarks	page about options	
Distribution: 1	Metal Ducts	Flue pipin	g: Plastic			
Filter: Standard	Filter Condition: Sa	ntisfactory				
Operated:	When turned on b	y thermostat	: ☑ Fired	☐ Did n	not fire	
Operation:	Satisfactory:	Yes □ No	☐ Recommend HVAC	techniciar	examine Before closing	
Controls:	□ Disconnect		✓ Normal operating a	nd safety c	controls observed	
Heat pump:	☐ Aux. Elec.	☐ Aux. Gas	☐ Aux. geothermal	☑ N/A		
	Emergency heat t	tested:	☐ Yes	□ No	☑ N/A	
HRV System:	☐ Yes	□ No	☐ Operated	□ Not c	pperated	
Others		☑ N/A				
	☐ Electric basebo	oard	☐ Radiant ceiling cable	☐ Gas s	space heater	
	☐ Radiant in floor	heating	☐ Wood burning stove	e (See Re	marks page)	
General Comme	ents					


Furnace was in normal working order at the time of the inspection. Filter should be changed /cleaned on regular bases. Unit is aged and is at or past its normal life expectancy; budget for replacement.

COOLING SYSTEM

System Components		□ None			Approximate a	ge: 15 to 20 yrs
Energy source: Electric						
Operated: Yes	Operation: Satisf	actory				
Refrigerant lines:	☐ Leak	☐ Damag	ged	☐ Insula	tion missing	☑ Satisfactory
Through wall unit(s):	☑ N/A	Operated:	☐ Yes	□ No	☐ Satisfactory	☐ Needs service
General Comments						
A/C unit was operating replacement.	in satisfactory cor	dition. Unit	is aged and	is at or pas	st its normal life expe	ctancy; budget for
		ELEC	CTRI	CAL		
Main Panel		Location	n: Basemer	ıt		
	Amps: 100 amps	•	Volts:120	/240 volts	Panel Type: Brea	akers
Appears grounded:	☑ Yes □ No	GFCI	present:	☐ Yes	☑ No Operates:	□ Yes □ No
Main Wire:	Not visible					
Branch Wire:	Copper					
	☑ Romex	☐ BX cal	ole	☐ Condui	t	☐ Knob & tube
	☐ Multiple tappin	g 🗆 Branch	n wires unde	ersized	☐ Federal Pacific pa	anel (see Remarks)
	☐ Multiple tappin	g of main disc	connect	☐ Safety	Hazard	
	☑ Arc fault prese		Operates:	☑ Y	es \square No \square N/A	(see Remarks)
	☐ Panel not acce	ssible	□ Not ev	aluated R	eason:	
Electrical Fixtures						
A representative number	r of installed light	ing fixtures,	switches, ar	nd receptac	eles located inside the	house, garage, and
exterior walls were teste				•		
	☑ Satisfactory	☐ Margir	nal	□ Poor		
	☐ Open grounds	☐ Revers	e polarity	☐ GFCIs 1	not operating Ungre	ounded 3-prong outlets
	☐ Solid conduct	or aluminuı	n branch v	viring circ	uits (See Rema	rks page)
	☐ Recommend	a licensed el	ectrician ev	aluate the	e service	
General Comments:						
Panel size appeared to b	e compatible to se	ervice size R	ranch break	er distribu	tion appeared normal	No signs of

Panel size appeared to be compatible to service size. Branch breaker distribution appeared normal. No signs of overheating were evident at the time of the inspection. Outlets were randomly tested and had correct polarity, except as noted.

PHOTO GALLERY



Pic. 1: Front view



Pic. 2: Roof covering





Pic. 4: Back view



Pic. 5: Back view



Pic. 6: AC unit 2005



Pic. 7: Garage



Pic. 8: Garage



Pic. 9: Attic



Pic. 10: Attic



Pic. 11: Attic



Pic. 12: Primary bedroom



Pic. 13: Primary bathroom



Pic. 14: Primary bathroom



Pic. 15: Primary bathroom




Pic. 16: Bedroom 2



Pic. 17: Joint ensuite





Pic. 19: Bedroom 3



Pic. 20: Bedroom 4



Pic. 21: Ensuite



Pic. 22: Dining room





Pic. 24: Eating area



Pic. 25: Kitchen



Pic. 26: Kitchen



Pic. 27: Kitchen



Pic. 28: Laundry



Pic. 29: Laundry



Pic. 30: Office





Pic. 34: Basement room



Pic. 37: Hot water tank 2018



Pic. 32: Rec room



Pic. 35: Basement bathroom



Pic. 38: Gas furnace 2005



Pic. 33: Rec room



Pic. 36: Basement bathroom



Pic. 39: 100 amp breaker panel

GENERAL REMARKS

List below are general remarks about the different areas and components of a home. These remarks are for general information purposes only and some of the information provided may not be specific to the home inspected.

GROUNDS REMARKS

Service Walks/Driveways

Spalling concrete cannot be patched with concrete because the new will not bond with the old. Water will freeze between the two layers, or the concrete will break up from movement or wear. Replacement of the damaged section is recommended. Walks or driveways that are close to the property should be properly pitched away to direct water away from the foundation. Asphalt driveways should be kept sealed and larger cracks filled so as to prevent damage from frost.

Patios that have settled towards the structure should be mudjacked or replaced to assure proper pitch. Improperly pitched patios are one source of wet basements.

Exterior Wood Surfaces

All surfaces of untreated wood need regular applications of paint or special chemicals to resist damage. Porch or deck columns and fence posts which are buried in the ground and made of untreated wood will become damaged within a year or two.

Decks should always be nailed with galvanized or aluminium nails. Decks that are not painted or stained should be treated with a water sealer.

Grading and Drainage

Any system of grading or landscaping that creates positive drainage (moving water away from the foundation walls) will help to keep a basement dry. Where negative grade exists and additional backfill is suggested, it may require digging out around the property to get a proper pitch. Dirt shall be approximately 15 cm below the bottom sill and should not touch wood surfaces.

Flower beds, loose mulched areas, railroad ties and other such landscaping items close to the foundation trap moisture and contribute to wet basements. To establish a positive grade, a proper slope away from the house is 2.5 cm per meter for approximately 1.5 to 2 meters. Recommend ground cover planting or grass to foundation.

Roof and Surface Water Control

Roof and surface water must be controlled to maintain a dry basement. This means keeping gutters cleaned out and aligned, extending downspouts, installing splash blocks, and building up the grade so that roof and surface water is diverted away from the building.

Window Wells

The amount of water which enters a window well from falling rain is generally slight, but water will accumulate in window wells if the yard is improperly graded. Plastic window well covers are useful in keeping out leaves and debris.

Retaining Walls

Retaining walls deteriorate because of excessive pressure build-up behind them, generally due to water accumulation. Often, conditions can be improved by excavating a trench behind the retaining wall and filling it with coarse gravel. Drain holes through the wall will then be able to relieve the water pressure.

Retaining walls sometime suffer from tree root pressure or from general movement of topsoil down the slope. Normally, these conditions require rebuilding the retaining wall.

Railings

It is recommended that railings be installed for any stairway over 3 steps and porches over 75 cm for safety reasons. Balusters for porches, balconies, and stairs should be close enough to assure children cannot squeeze through.

ROOF COVERING REMARKS

Valleys & Flashings

Valleys and flashings that are covered with shingles and/or tar or any other material are considered not visible and are not part of the inspection.

Stone Roofs - Coverings

This type of covering on a pitched roof requires ongoing annual maintenance. We recommend that a roofing contractor evaluate this type of roof. Infra-red photography is best used to determine areas of potential leaks.

Flat Roofs

Flat roofs are very vulnerable to leaking. It is very important to maintain proper drainage to prevent ponding of water. We recommend that a roofing contractor evaluate this type of roof.

ROOF TYPE	LIFE EXPECTANCY	SPECIAL REMARKS
Asphalt Shingles	15-20 years	Used on nearly 80% of all residential roofs; requires little maintenance
Asphalt Multi-Thickness Shingles*	20-30 years	Heavier and more durable than regular asphalt shingles
Asphalt Interlocking Shingles*	15-25 years	Especially good in high-wind areas
Asphalt Rolls	10 years	Used on low slope roofs
Built-up Roofing	10-20 years	Used on low slope roofs; 2 to 3 times as costly as asphalt shingles
Wood Shingles*	10-40 years ¹	Treat with preservative every 5 years to prevent decay
Clay Tiles* Cement Tiles*	20 + years 20 + years	Durable, fireproof, but not watertight, requiring a good subsurface base
Slate Shingles*	30-100 years ²	Extremely durable, but brittle and expensive
Asbestos Cement Shingles*	30-75 years	Durable, but brittle and difficult to repair
Metal Roofing	15-40 + years	Comes in sheets & shingles; should be well grounded for protection from lightning; certain metals must be painted
Single Ply Membrane	15-25 years (mfgr's claim)	New material; not yet passed test of time

Roof covering should be visually checked in spring and fall for any visible missing shingles, damaged coverings or other defects. Before re-roofing, the underside of the roof structure and roof sheathing should be inspected to determine that the roof structure can support the additional weight of the shingles.

Wood shakes and shingles will vary in aging, due to quality of the material, installation, maintenance, and surrounding shade trees. Ventilation and drying of the wood material is critical in extending the life expectancy of the wood. Commercial preservatives are available on the market, which could be applied to wood to impede deterioration.

^{*} Not recommended for use on low slope roof 1 Depending on local conditions and proper installation

² Depending on quality of slate

CHIMNEY / GUTTERS / SIDING / TRIM REMARKS

Chimneys

Chimneys built of masonry will eventually need tuck pointing. A cracked chimney top that allows water and carbonic acid to get behind the surface brick/stone will accelerate the deterioration. Moisture will also deteriorate the clay flue liner. Periodic chimney cleaning will keep you apprised of the chimney's condition. The flashing around the chimney may need resealing and should be inspected every year or two. Fireplace chimneys should be inspected and evaluated by a chimney professional before using. Chimneys must be adequate height for proper drafting. Spark arrestors are recommended for wood burning chimney and chimney caps for fossil fuels

Unlined Chimney - should be re-evaluated by a chimney technician.

Have flue cleaned and re-evaluated. The flue lining is covered with soot or creosote and no representation can be made as to the condition.

NOT EVALUATED- The flue was not evaluated due to inaccessibility such as roof pitch, cap, cleanout not accessible, etc.

Cricket Flashing

Small, sloped structure made of metal and designed to drain moisture away from a chimney. Crickets are usually placed at the back of a chimney.

Gutters and Downspouts

This is an extremely important element in basement dampness control. Keep gutters clean and downspout extensions in place (1.25 meters or more). Paint the inside of galvanized gutters, which will extend the life. Shortly after a rain or thaw in winter, look for leaks at seams in the gutters. These can be re-caulked before they cause damage to fascia or soffit boards. If no gutters exist, it is recommended that they be added.

Siding

Wood siding should not come in contact with the ground. The moisture will cause rotting to take place and can attract carpenter ants.

EIFS - This type of siding has experienced serious problems and requires a certified EIFS inspector to determine condition.

Brick and stone veneer must be monitored for loose or missing mortar. Some brick and stone are susceptible to spalling. This can be caused when moisture is trapped and a freeze/thaw situation occurs. There are products on the market that can be used to seal out the moisture. This holds true for brick and stone chimneys also.

Metal sidings will dent and scratch. Oxidation is a normal reaction in aluminum. There are good cleaners on the market and it is recommended that they be used occasionally. Metal siding can be painted.

Doors and Windows

These can waste an enormous amount of energy. Maintain the caulking around the frames on the exterior. Check for drafts in the winter and improve the worst offenders first. Windows that have leaky storm windows will usually have a lot of sweating. Likewise, well-sealed storms that sweat indicate a leaky window. It is the tighter unit that will sweat (unless the home has excess humidity to begin with.)

Wood that exhibits blistering or peeling paint should be examined for possible moisture sources: roof leaks, bad gutters, interior moisture from baths or laundry or from a poorly vented crawl space. Some paint problems have no logical explanation, but many are a symptom of an underlying problem. A freshly painted house may mask these symptoms, but after you have lived in the home for a year or two, look for localized paint blistering (peeling). It may be a clue.

New glazing will last longer if the raw wood is treated with boiled linseed oil prior to glazing. It prevents the wood from drawing the moisture out of the new glazing.

Caulking

Many different types of caulk are available on the market today. Check with a paint or hardware store for the kind of application you need.

EXTERIOR / ELECTRICAL / AC / GARAGE REMARKS

Exterior Doors

The exposed side of wood exterior doors needs to be painted or stained and varnished to prevent discolouring and delamination. Weather-stripping is a must to prevent drafts.

Electrical

Overhead wires from the mast to the main panel that are exposed to the weather may fray and crack. If this occurs, wires should be replaced by a licensed electrician.

Any outdoor overhead service conductor wires should have adequate clearance above the ground (3 meters) and from balcony and windows (1 meter), for safety reasons.

Underground system - Some exterior boxes that are at ground level have a grade line on them. You should insure that the grade remains below this line to prevent moisture from entering the main panel.

Overhead Door Openers

We recommend that a separate electrical outlet be provided. Openers that do not have a safety reverse are considered a safety hazard. Small children and pets are especially vulnerable. We recommend the operating switches be set high enough so children cannot reach them. If an electric sensor is present, it should be tested occasionally to ensure it is working.

Garage Sill Plates

Sill plates within the garage should be elevated or treated lumber should be used. If this is not the case, try to direct water away to prevent rotting.

A/C Compressors

They should not become overgrown with foliage. Clearance requirements vary, but 60 cm on all sides should be considered minimal with up to 2 meters of air discharge desirable. If a clothes dryer vent is within five to ten feet, either relocate the vent or do not run when the A/C is running. The lint will quickly reduce the efficiency of the A/C unit.

Burners

Any appliance such as a water heater, furnace, etc. should have the flame a minimum of 45 cm above the floor. Any open flame less than 45 cm from the floor is a potential safety hazard. The appliance should also be protected from vehicle damage.

KITCHEN / LAUNDRY / UTILITY ROOM REMARKS

Plaster on Wood Lath

Plaster on wood lath is an old technique and is no longer in general use. Wood lath shrinks with time and the nails rust and loosen. As a result, the plaster may become fragile and caution is needed in working with this type of plastering system. Sagging ceilings are best repaired by laminating drywall over the existing plaster and screwing it to the ceiling joists.

Plaster on Gypsum Lath (Rock Lath)

Plaster on gypsum lath will sometimes show the seams of the 40 cm wide gypsum lath, but this does not indicate a structural fault. The scalloping appearance can be levelled with drywall joint compound and fibreglass mesh joint tape or drywall can be laminated over the existing plaster on the ceiling.

Wood Flooring

Always attempt to clean wood floors first before making the decision to refinish the floor. Wax removers and other mild stripping agents plus a good waxing and buffing will usually produce satisfactory results. Mild bleaching agents help remove deep stains. Sanding removes some of the wood in the floor and can usually be done safely only once or twice in the life of the floor.

Nail Pops

Drywall nail pops are due to normal expansion and contraction of the wood members to which the drywall is nailed, and are usually of no structural significance.

Carpeting

Where carpeting has been installed, the materials and condition of the floor underneath cannot be determined.

Appliances

Dishwashers are tested to see if the motor operates and water sprays properly (full cycles are not run). Stoves are tested to see that burners are working and oven and broiler get hot. Timer and controls are not tested. Refrigerators are not tested.

No representation is made to continued life expectancy of any appliance.

Asbestos and Other Hazards

Asbestos fibres in some form are present in many homes, but are often not visible and cannot be identified without testing.

If there is reason to suspect that asbestos may be present and if it is of particular concern, a sample of the material in question may be removed and analyzed in a laboratory. *However, detecting or inspecting for the presence or absence of asbestos is not a part of our inspection.*

Also excluded from this inspection and report are the possible presence of, or danger from, radon gas, lead-based paint, urea formaldehyde, toxic or flammable chemicals and all other similar or potentially harmful substances and environmental hazards.

Windows

A representative number of windows are inspected.

BATHROOM REMARKS

Stall Shower

The metal shower pan in a stall shower has a potential or probable life of 10-20 years depending on quality of the pan installed. Although a visible inspection is made to determine whether a shower pan is currently leaking, it cannot be stated with certainty that no defect is present or that one may not soon develop. Shower pan leaks often do not show except when the shower is in actual use.

Ceramic Tile

Bathroom tile installed in a mortar bed is excellent. It is still necessary to keep the joint between the tile and the tub/shower caulked or sealed to prevent water spillage from leaking through and damaging the ceilings below.

Ceramic tile is often installed in mastic. It is important to keep the tile caulked or water will seep behind the tile and cause deterioration in the wallboard. Special attention should be paid to the area around faucets and other tile penetrations.

Exhaust Fans

Bathrooms with a shower should have exhaust fans where possible. This helps to remove excess moisture from the room, preventing damage to the ceiling and walls and wood finishes. The exhaust fan should not be vented into the attic. The proper way to vent the fans is to the outside. Running the vent pipe horizontally and venting into a gable end or soffit is preferred. Running the vent pipe vertically through the roof may cause condensation to run down the vent pipe, rusting the fan and damaging the wallboard. Insulating the vent pipe in the attic will help to reduce this problem.

SLOW DRAINS on sinks, tubs, and showers are usually due to build-up of hair and soap scum. Most sink pop-ups can be easily removed for cleaning. Some tubs have a spring attached to the closing lever that acts as a catch for hair. It may require removing a couple of screws to disassemble. If you cannot mechanically remove the obstruction, be kind to your pipes. Don't use a caustic cleaner. There are several bacteria drain cleaners available. They are available at hardware stores in areas where septic tanks are used. These drain cleaners take a little longer to work, but are safe for you and your pipes.

Safety Hazards

Typical safety hazards found in bathrooms are open grounds or reverse polarity by water. Replacing these outlets with G.F.C.I.'s are recommended. (See Electrical section)

Whirlpool Tubs

This relates to interior tubs hooked up to interior plumbing. Where possible, the motor will be operated to see that the jets are working. Hot tubs and spas are not inspected.

ROOMS (INTERIOR) REMARKS

Door Stops

All swinging doors should be checked for door stops. Broken or missing door stops can result in door knobs breaking through drywall or plaster.

Closet Guides

Sliding closet doors should be checked to see that closet guides are in place. Missing or broken closet guides can cause scratches and damage to doors.

Cold Air Returns

Bedrooms that do not have cold air returns in them should have a 1.75 cm gap under the doors to allow cold air to be drawn into the hall return.

AN INSPECTION VERSUS A WARRANTY

A home inspection is just what the name indicates, an inspection of a home...usually a home that is being purchased. The purpose of the inspection is to determine the condition of the various systems and structures of the home. While an inspection performed by a competent inspection firm will determine the condition of the major components of the home, no inspection will pick up every minute latent defect. The inspector's ability to find all defects is limited by access to various parts of the property, lack of information about the property and many other factors. A good inspector will do his or her level best to determine the condition of the home and to report it accurately. The report that is issued is an opinion as to the condition of the home. This opinion is arrived at by the best technical methods available to the home inspection industry. It is still only an opinion.

A warranty is a policy sold to the buyer that warrants that specific items in the home are in sound condition and will remain in sound condition for a specified period of time. Typically, the warranty company never inspects the home. The warranty company uses actuarial tables to determine the expected life of the warranted items and charges the customer a fee for the warranty that will hopefully cover any projected loss and make a profit for the warranty seller. It is essentially an insurance policy.

The service that we have provided you is an inspection. We make no warranty of this property. If you desire warranty coverage, please see your real estate agent for details about any warranty plan to which their firm may have access.

WINDOWS / FIREPLACES / ATTIC REMRKS

Window Frames and Sills

Window frames and sills often are found to have surface deterioration due to condensation that has run off the window and damaged the varnish. Usually this can be repaired with a solvent style refinisher and fine steel wool. This is sometimes a sign of excess humidity in the house.

See comments regarding caulking doors and windows above (Chimneys/Gutters/Siding).

Fireplaces

It is important that a fireplace be cleaned on a routine basis to prevent the build-up of creosote in the flue, which can cause a chimney fire.

Masonry fireplace chimneys are normally required to have a terra cotta flue liner or 8 inches of masonry surrounding each flue in order to be considered safe and to conform to most building codes.

During visual inspections, it is not uncommon to be unable to detect the absence of a flue liner either because of stoppage at the firebox, a defective damper or lack of access from the roof.

Wood burners

Once installed, it can be difficult to determine proper clearances for wood burning stoves. Manufacturer specifications, which are not usually available to the inspector, determine the proper installation. We recommend you ask the owner for paperwork verifying that it was installed by a professional contractor.

Ventilation

Ventilation is recommended at the rate of one square foot of vent area to 300 square feet of attic floor space, this being divided between soffit and rooftop. Power vents should ideally have both a humidistat and a thermostat, since ventilation is needed to remove winter moisture as well as summer heat. Evidence of condensation, such as blackened roof sheathing, frost on nail heads, etc. is an indication that ventilation may have been or is blocked or inadequate.

Insulation

The recommended insulation in the attic area is R-38, approximately 30cm. If insulation is added, it is important that the ventilation is proper.

Smoke Detectors

Smoke detectors should be tested monthly. At least one detector should be on each level.

Vapour Barriers

The vapour barrier should be on the warm side of the surface. Older homes were often built without vapour barriers. If the vapour barrier is towards the cold side of the surface, it should be sliced or removed. Most vapour barriers in the attic are covered by insulation and therefore, not visible.

Safety Glazing

Safety glazing requirements vary depending on the age of the home. Every attempt is made to identify areas where the lack of safety glazing presents an immediate safety hazard, such as a shower door. In some older homes it is difficult to determine if safety glazing is present, since the glass is not marked. Therefore, no representation is made that safety glazing exists in all appropriate areas.

Insulated Glass

The broken seals are not always detectable due to dirty windows, covered windows, etc. In most cases, leaking glass seals take some time before they are evident.

BASEMENT REMARKS

Basement

Any basement that has cracks or leaks is technically considered to have failed. Most block basements have step cracks in various areas. If little or no movement has occurred, and the step cracks are uniform, this is considered acceptable. Horizontal cracks in the third or fourth block down indicate the block has moved due to outside pressure. They can be attributed to many factors, such as improper grading, improperly functioning gutter and downspout system, etc. Normally, if little or no movement has taken place and proper grading and downspouts exist, this is considered acceptable. If the wall containing the stress crack(s) has moved considerably, this will require some method of reinforcement. Basements that have been freshly painted or tuck-pointed should be monitored for movement. This will be indicated by cracks reopening. If cracks reappear, reinforcement may be necessary. Reinforcing a basement wall can become expensive.

Foundation (Covered Walls)

Although an effort has been made to note any major inflections or weaknesses, it is difficult at best to detect these areas when walls are finished off, or basement storage makes areas inaccessible. *No representation is made as to the condition of these walls.*

Monitor indicates that the walls have stress cracks, but little movement has occurred. In our opinion, the cracks should be filled with mortar and the walls monitored for further movement and cracking. If additional movement or cracking occurs, re-enforcements may be necessary.

Have Evaluated — we recommend that the walls be re-evaluated by a structural engineer or basement repair company and estimates be obtained if work is required.

Vapour Barrier

Floors that are dirt or gravel should be covered with a vapour barrier.

Moisture Present

Basement dampness is frequently noted in houses and in most cases the stains, moisture or efflorescence present is a symptom denoting that a problem exists outside the home. Usual causes are improper downspout extensions or leaking gutters and/or low or improper grade (including concrete surfaces) at the perimeter of the house. A proper slope away from the house is one inch per foot for four to six feet.

Expensive solutions to basement dampness are frequently offered, and it is possible to spend thousands of dollars on solutions such as pumping out water that has already entered or pumping of chemical preparations into the ground around the house, when all that may be necessary are a few common sense solutions at the exterior perimeter. However, this is not intended to be an exhaustive list of causes and solutions to the presence of moisture. *No representation is made to future moisture that may appear.*

Palmer Valve

Many older homes have a valve in the floor drain. This drain needs to remain operational.

Drain Tile

We offer no opinion about the existence or condition of the drain tile, as it cannot be visibly inspected.

Basement Electrical Outlets

We recommend that you have an outlet within 2 meters of each appliance. The appliance you plan to install may be different than what exists; therefore the inspection includes testing a representative number of receptacles that exist. It is also recommended to have ground fault circuit interrupts for any outlet in the unfinished part of the basement and crawl spaces.

PLUMBING REMARKS

Wells

Examination of wells is not included in this visual inspection. It is recommended that you have well water checked for purity by the local health authorities and, if possible, a check on the flow of the well in periods of drought. A well pit should have a locked cover on it to prevent anyone from falling into the pit.

Septic Systems

The check of septic systems is not included in our visual inspection. You should have the local health authorities or other qualified experts check the condition of a septic system.

In order for the septic system to be checked, the house must have been occupied within the last 30 days.

Water Pipes

Galvanized water pipes rust from the inside out and may have to be replaced within 20 to 30 years. This is usually done in two stages: horizontal piping in the basement first and vertical pipes throughout the house later as needed.

Copper pipes usually have more life expectancy and may last as long as 60 years before needing to be replaced.

Polybutylene pipes are grey pipes that have a history of failure and should be examined by a licensed plumber.

Hose Bibs

During the winter months it is necessary to make sure the outside faucets are winterized. This can be done by means of a valve located in the basement. Leave the outside faucets open to allow any water standing in the pipes to drain, preventing them from freezing. Hose bibs cannot be tested when winterized.

Water Heater

The life expectancy of a water heater is 5-10 years. Water heaters generally need not be replaced unless they leak. It is a good maintenance practice to drain 5-10 gallons from the heater several times a year. *Missing relief valves or improper extension present a safety hazard.*

Water Softeners

During a visual inspection, it is not possible to determine if water is being properly softened.

Plumbing

The temperature/pressure valve should be tested several times a year by lifting the valve's handle. Caution: very hot water will be discharged. If no water comes out, the valve is defective and must be replaced.

Shut-Off Valves

Most shut-off valves have not been operated for long periods of time. We recommend operating each shut-off valve to: toilet bowl, water heater, under sinks, main shut-off, hose faucets, and all others. We recommend you have a plumber do this, as some of the valves may need to be repacked or replaced. Once the valves are in proper operating order, we recommend opening and closing these valves several times a year.

Polybutylene Piping

This type of piping has a history of problems and should be examined by a licensed plumber and repaired or replaced as necessary.

MECHANICAL DEVICES MAY OPERATE AT ONE MOMENT AND LATER MALFUNCTION; THEREFORE, LIABILITY IS SPECIFICALLY LIMITED TO THOSE SITUATIONS WHERE IT CAN BE CONCLUSIVELY SHOWN THAT THE MECHANICAL DEVICE INSPECTED WAS INOPERABLE OR IN THE IMMEDIATE NEED OF REPAIR OR NOT PERFORMING THE FUNCTION FOR WHICH IS IT WAS INTENDED AT THE TIME OF INSPECTION.

HEATING SYSTEM REMARKS

HEATING AND AIR CONDITIONING units have limited lives. Normal lives are:

GAS-FIRED HOT AIR15-25	<i>years</i>
OIL-FIRED HOT AIR20-30) years
CAST IRON BOILER30-50) years
(Hot water or steam) or mo	ore
STEEL BOILER30-40) years
(Hot water or steam) or mo	ore
COPPER BOILER10-20) years
(Hot water or steam)	
CIRCULATING PUMP (Hot water)10-15	years
AIR CONDITIONING COMPRESSOR8-12	years
HEAT PUMP8-12	years

Gas-fired hot air units that are close to or beyond their normal lives have the potential of becoming a source of carbon monoxide in the home. You may want to have such a unit checked every year or so to assure yourself that it is still intact. Of course, a unit of such an age is a good candidate for replacement with one of the new, high efficiency furnaces. The fuel savings alone can be very attractive.

Boilers and their systems may require annual attention. If you are not familiar with your system, have a heating contractor come out in the fall to show you how to do the necessary things. *Caution: do not add water to a hot boiler!*

Forced air systems should have filters changed every 30 to 60 days of the heating and cooling season. This is especially true if you have central air conditioning. A dirty air system can lead to premature failure of your compressor - a \$1,500 machine.

Oil-fired furnaces and boilers should be serviced by a professional each year. Most experts agree you will pay for the service cost in fuel saved by having a properly tuned burner.

Read the instructions for maintaining the humidifier on your furnace. A malfunctioning humidifier can rust out a furnace rather quickly. It is recommended that the humidifier be serviced at the same time as the furnace, and be cleaned regularly. *During a visual inspection it is not possible to determine if the humidifier is working.*

Have HVAC Technician Examine - A condition was found that suggests a heating contractor should do a further analysis. We suggest doing this before closing.

Heat exchangers cannot be examined nor their condition determined without being disassembled. Since this is not possible during a visual, non-technically exhaustive inspection, you may want to obtain a service contract on the unit or contact a furnace technician regarding a more thorough examination.

Testing pilot safety switch requires blowing out the pilot light. Checking safety limit controls requires disconnecting blower motor or using other means beyond the scope of this inspection. If furnace has not been serviced in last 12 months, you may want to have a furnace technician examine.

CO Test - This is not part of a non-technical inspection.

Combustible Gas Test (Potential Safety Hazard) - If a combustible gas detector was used during the inspection of the furnace and evidence of possible combustible gases was noted, we caution you that our test instrument is sensitive to many gases and not a foolproof test. None-the-less, this presents the <u>possibility</u> that a hazard exists and could indicate that the heat exchanger is, or will soon be, defective.

COOLING SYSTEM / ELECTRICAL REMARKS

Electrical

Every effort has been made to evaluate the size of the service. Three wires going into the home indicate 240 volts. The total amps are sometimes difficult to determine. We highly recommend that ground fault circuit interrupters (G.F.C.I.) be connected to all outlets around water. This device automatically opens the circuit when it senses a current leak to ground. This device can be purchased in most hardware stores. G.F.C.I.'s are recommended by all outlets located near water, outside outlets, or garage outlets. Pool outlets should also be protected with a G.F.C.I.

The G.F.C.I. senses the flow of electricity through a circuit. If more current is flowing through the black ("hot") wire than the white ("neutral") wire, there is a current leakage. The G.F.C.I., which can sense a ground leak of as little as .005 amps, will shut off the current in 1/40 of a second, which is fast enough to prevent injury.

If you do have G.F.C.I.'s, it is recommended that you test (and reset) them monthly. When you push the test button, the reset button should pop out, shutting off the circuit. If it doesn't, the breaker is not working properly. If you don't test them once a month, the breakers have a tendency to stick, and may not protect you when needed.

Knob and tube wiring found in older homes should be checked by an electrician to insure that the wire cover is in good condition. Under no circumstances should this wire be covered with insulation. Recess light fixtures should have a baffle around them so that they are not covered with insulation. The newer recessed fixtures will shut off if they overheat.

Federal Pacific electrical panels may be unsafe. See www.google.com and search for "Federal Pacific" for additional and up-to-date information.

Aluminum wiring in general lighting circuits has a history of overheating, with the potential of a fire. If this type of wiring exists, a licensed electrical contractor should examine the whole system.

Arc Faults

In some areas, arc faults are required in new homes, starting in 2002. These control outlets in the bedrooms.

Reverse Polarity

A common problem that surfaces in many homes is reverse polarity. This is a potentially hazardous situation in which the hot and neutral wires of a circuit are reversed at the outlet, thereby allowing the appliance to incorrectly be connected. This is an inexpensive item to correct.

Each receptacle has a brass and silver screw. The black wire should be wired to the brass screw and the white wire should go to the silver screw. When these wires are switched, this is called "reverse polarity". Turning off the power and switching these wires will correct the problem.

Main service wiring for housing is typically 240 volts. The minimum capacity for newer homes is 100 amps, though many older homes still have 60 amp service. Larger homes or all electric homes will likely have a 200 amp service.

Main service wiring may be protected by one or more circuit breakers or fuses. While most areas allow up to six main turnoffs, expanding from these panels is generally not allowed.

Cooling

Testing A/C System and Heat Pump - The circuit breakers to A/C should be on for a minimum of 24 hours and the outside temperature at least 15 ° C for the past 24 hours or an A/C system cannot be operated without possible damage to the compressor. Check the instructions in your A/C manual or on the outside compressor before starting up in the summer. Heat pump can only be tested in the mode it's running in. Outside temperature should be at least 15 ° C for the past 24 hours to run in cooling mode.

Temperature differential, between 7°-15°, is usually acceptable. If out of this range, have an HVAC contractor examine it. It is not always feasible to do a differential test due to high humidity, low outside temperature, etc.

HOME MAINTENANCE SCHEDULE

Regular Maintenance Is the Key

Inspecting your home on a regular basis and following good maintenance practices is the best way to protect your investment in your home. Whether you take care of a few tasks at a time or several all at once, it is important to get into the habit of doing them. Establish a routine for yourself and you will find the work is easy to accomplish and not very time consuming. A regular schedule of seasonal maintenance can put a stop to the most common — and costly — problems, before they occur. If necessary use a camera to take pictures of anything you might want to share with an expert for advice or to monitor or remind you of a situation later.

By following the information noted here, you will learn about protecting your investment and how to help keep your home a safe and healthy place to live.

If you do not feel comfortable performing some of the home maintenance tasks listed below, or have the necessary equipment, for example a ladder, you may want to consider hiring a qualified handy person to help you.

Seasonal Home Maintenance

Most home maintenance activities are seasonal. Fall is the time to get your home ready for the coming winter, which can be the most grueling season for your home. During winter months, it is important to follow routine maintenance procedures, by checking your home carefully for any problems arising and taking corrective action as soon as possible. Spring is the time to assess winter damage, start repairs and prepare for warmer months. Over the summer, there are a number of indoor and outdoor maintenance tasks to look after, such as repairing walkways and steps, painting and checking your chimney and roof.

While most maintenance is seasonal, there are some things you should do on a frequent basis year round:
Make sure air vents indoors and outside (intake, exhaust and forced air) are not blocked by snow or debris.
Check and clean range hood filters on a monthly basis.
Test the ground fault circuit interrupter(s) monthly by pushing the test button, which should then cause the reset button to pop up.
If there are young children in the house, make sure electrical outlets are equipped with safety plugs.
Regularly check the house for safety hazards such as a loose handrail, lifting or buckling carpet, etc.

Timing of the seasons varies not only from one area of Canada to another, but also from year to year in a given area. For this reason, we have not identified the months for each season. The maintenance schedule presented here, instead, is a general guide for you to follow. The actual timing is left for you to decide, and you may want to further divide the list of items for each season into months.

Fall

Have furnace or heating system serviced by a qualified service company every two years for a gas furnace, and every year for an oil furnace.
Open furnace humidifier damper on units with central air conditioning and clean humidifier.
Lubricate circulating pump on hot water heating system.
Bleed air from hot water radiators.
Examine the forced air furnace fan belt for wear, looseness or noise; clean fan blades of any dirt buildup (after disconnecting the electricity to the motor first).
Turn ON gas furnace pilot light.
Check and clean or replace furnace air filters each month during the heating season. Ventilation system, such as heat recovery ventilator, filters should be checked every two months.
Vacuum electric baseboard heaters to remove dust.
Remove the grilles on forced air systems and vacuum inside the ducts.
If the heat recovery ventilator has been shut off for the summer, clean the filters and the core, and pour water down the condensate drain to test it.
Clean portable humidifier, if one is used.
Have well water tested for quality. It is recommended that you test for bacteria every six months.
Check sump pump and line to ensure proper operation, and to ascertain that there are no line obstructions or visible leaks.
Replace window screens with storm windows.
Remove screens from the inside of casement windows to allow air from the heating system to keep condensation off window glass.
Ensure all doors to the outside shut tightly, and check other doors for ease of use. Renew door weatherstripping if required.
If there is a door between your house and the garage, check the adjustment of the self-closing device to ensure it closes the door completely.
Ensure windows and skylights close tightly.
Cover outside of air conditioning units.
Ensure that the ground around your home slopes away from the foundation wall, so that water does not drain into your basement.
Clean leaves from eaves troughs and roofs, and test downspouts to ensure proper drainage from the roof.
Check chimneys for obstructions such as nests.
Drain and store outdoor hoses. Close valve to outdoor hose connection and drain the hose bib (exterior faucet), unless your house has frost proof hose bibs.
If you have a septic tank, measure the sludge and scum to determine if the tank needs to be emptied before the spring. Tanks should be pumped out at least once every three years.
Winterize landscaping, for example, store outdoor furniture, prepare gardens and, if necessary, protect young trees or bushes for winter.

Winter

Check and clean or replace furnace air filters each month during the heating season. Ventilation system, such as heat recovery ventilator, filters should be checked every two months.
After consulting your hot water tank owner's manual, drain off a dishpan full of water from the clean-out valve at the bottom of your hot water tank to control sediment and maintain efficiency.
Clean humidifier two or three times during the winter season.
Vacuum bathroom fan grille.
Vacuum fire and smoke detectors, as dust or spider webs can prevent them from functioning.
Vacuum radiator grilles on back of refrigerators and freezers, and empty and clean drip trays.
Check gauge on all fire extinguishers; recharge or replace if necessary.
Check fire escape routes, door and window locks and hardware, and lighting around outside of house; ensure family has good security habits.
Check the basement floor drain to ensure the trap contains water. Refill with water if necessary.
Monitor your home for excessive moisture levels—for example, condensation on your windows, which can cause significant damage over time and pose serious health problems—and take corrective action.
Check all faucets for signs of dripping and change washers as needed. Faucets requiring frequent replacement of washers may be in need of repair.
If you have a plumbing fixture that is not used frequently, such as a laundry tub or spare bathroom sink, tub or shower stall, run some water briefly to keep water in the trap.
Clean drains in dishwasher, sinks, bathtubs and shower stalls.
Test plumbing shut-off valves to ensure they are working and to prevent them from seizing.
Examine windows and doors for ice accumulation or cold air leaks. If found, make a note to repair or replace in the spring.
Examine attic for frost accumulation. Check roof for ice dams or icicles. If there is excessive frost or staining of the underside of the roof, or ice dams on the roof surface.
Check electrical cords, plugs and outlets for all indoor and outdoor seasonal lights to ensure fire safety: if worn, or plugs or cords feel warm to the touch, replace immediately.

Spring

	After consulting your hot water tank owner's manual, carefully test the temperature and pressure relief valve to ensure it is not stuck. (Caution: This test may release hot water that can cause burns.)
	Check and clean or replace furnace air filters each month during the heating season. Ventilation system, for example heat recovery ventilator, filters should be checked every two months.
	Have fireplace or woodstove and chimney cleaned and serviced as needed.
	Shut down and clean furnace humidifier, and close the furnace humidifier damper on units with central air conditioning.
	Check air conditioning system and have serviced every two or three years.
	Clean or replace air conditioning filter (if applicable).
	Check dehumidifier and clean if necessary.
	Turn OFF gas furnace and fireplace pilot lights where possible.
	Have well water tested for quality. It is recommended that you test for bacteria every six months.
	Check smoke, carbon monoxide and security alarms and replace batteries.
	Clean windows, screens and hardware, and replace storm windows with screens. Check screens first and repair or replace if needed.
	Open valve to outside hose connection after all danger of frost has passed.
	Examine the foundation walls for cracks, leaks or signs of moisture, and repair as required. Repair and paint fences as necessary.
	Ensure sump pump is operating properly before the spring thaw sets in. Ensure discharge pipe is connected and allows water to drain away from the foundation.
	Re-level any exterior steps or decks which moved due to frost or settling.
	Check eaves troughs and downspouts for loose joints and secure attachment to your home, clear any obstructions, and ensure water flows away from your foundation.
	Clear all drainage ditches and culverts of debris.
П	Undertake spring landscape maintenance and, if necessary, fertilize young trees.

Summer

Monitor basement humidity and avoid relative humidity levels above 60 per cent. Use a dehumidifier to maintain safe relative humidity. Clean or replace air conditioning filter, and wash or replace ventilation system filters if necessary.
Check basement pipes for condensation or dripping, and take corrective action, for example, reduce humidity and or insulate cold water pipes.
Check the basement floor drain to ensure the trap contains water. Refill with water if necessary.
If you have a plumbing fixture that is not used frequently, for example, a laundry tub or spare bathroom sink, tub or shower stall, run some water briefly to keep water in the trap.
Deep clean carpets and rugs.
Vacuum bathroom fan grille.
Disconnect the duct connected to the dryer and vacuum lint from duct, the areas surrounding your clothes dryer and your dryer's vent hood outside.
Check security of all guardrails and handrails.
Check smooth functioning of all windows and lubricate as required.
Inspect window putty on outside of glass panes and replace if needed.
Lubricate door hinges and tighten screws as needed.
Lubricate garage door hardware and ensure it is operating properly.
Lubricate automatic garage door opener motor, chain, etc. and ensure that the auto-reverse mechanism is properly adjusted.
Check and replace damaged caulking and weather-stripping around windows and doorways, including the doorway between the garage and the house.
Inspect electrical service lines for secure attachment where they enter your house, and make sure there is no water leakage into the house along the electrical conduit.
Check exterior wood siding and trim for signs of deterioration; clean, replace or refinish as needed.
Check for and seal off any holes in exterior cladding that could be an entry point for small pests, such as bats, squirrels.
Remove any plants that contact, or roots that penetrate the siding or brick.
Climb up on your roof, or use binoculars, to check its general condition, and note any sagging, that could indicate structural problems requiring further investigation from inside the attic. Note the condition of all shingles for possible repair or replacement, and examine all roof flashings, such as at chimney and roof joints, for any signs of cracking or leakage.
Sweep chimneys connected to any wood burning appliance or fireplace, and inspect them for end-of-season problems.
Check the chimney cap and the caulking between the cap and the chimney.
Repair driveway and walkways as needed.
Repair any damaged steps that present a safety problem.